


NOTE: A drilled hole (finish d^{H13}) is adequate. Don't ream the hole.



Straight Brass Plug Baffles (Inch) – BB

ITEM NUMBER	NOMINAL PLUG SIZE	HEX SIZE S	NOMINAL LENGTH OVERALL	BAFFLE THICKNESS	BAFFLE WIDTH -.005 -.015	DRILL SIZE	C
BB-05-4	1/16	5/32	4"	.050	1/4	1/4	.10
BB-05-8	1/16	5/32	8"	.050	1/4	1/4	.10
BB-10-4	1/8	3/16	4"	1/16	5/16	5/16	.12
BB-10-8	1/8	3/16	8"	1/16	5/16	5/16	.12
BB-20-5	1/4	1/4	5"	3/32	7/16	7/16	.17
BB-20-10	1/4	1/4	10"	3/32	7/16	7/16	.17
BB-40-6	3/8	5/16	6"	3/32	9/16	9/16	.21
BB-40-12	3/8	5/16	12"	3/32	9/16	9/16	.21
BB-60-8	1/2	3/8	8"	3/32	11/16	11/16	.26
BB-60-16	1/2	3/8	16"	3/32	11/16	11/16	.26
BB-100-12	3/4	9/16	12"	1/8	15/16	15/16	.35
BB-100-20	3/4	9/16	20"	1/8	15/16	15/16	.35
BB-140-16	1	5/8	16"	1/8	1 1/8	1 1/8	.42
BB-140-24	1	5/8	24"	1/8	1 1/8	1 1/8	.42

ITEM NUMBER	R	SW	B	L	L1	T	d
BB-100-18	1/8" BSP	5	8.2	100	8	2.0	8.5
BB-200-18	1/8" BSP	5	8.2	200	8	2.0	8.5
BB-125-14	1/4" BSP	6	11.2	125	10	2.5	11.5
BB-250-14	1/4" BSP	6	11.2	250	10	2.5	11.5
BB-150-38	3/8" BSP	8	14.7	150	10	2.5	15.0
BB-300-38	3/8" BSP	8	14.7	300	10	2.5	15.0
BB-200-12	1/2" BSP	10	18.2	200	10	2.5	18.5
BB-400-12	1/2" BSP	10	18.2	400	10	2.5	18.5
BB-300-34	3/4" BSP	12	23.2	300	12	3.0	23.5
BB-500-34	3/4" BSP	12	23.2	500	12	3.0	23.5