



**LSPM** (L-shaped swivel type — Constant flow type—)

※Socket connection section

M Body: Brass (C3604)  
 Inner parts: Brass (C2700W)  
 Fluoric rubber  
 Fluoric rubber grease

⚠ Hexagonal hole bored at the tapered screw end.      Thread JIS B0203 tapered thread for tubing R(PT)

**LSP** (L-shaped swivel type)

※Socket connection section

M Brass (C3604)

⚠ Hexagonal hole bored at the tapered screw end.      Thread JIS B0203 tapered thread for tubing R(PT)

Matching Sockets	Socket connection parts		L1	L2	Allen side B	Hexagonal wrench socket $\odot$ d	Tapered thread R(PT)	$l_1$	Part Number	
	V	l							Type	No.
Mold Coupler Series Socket hole diameter V=8 Common to all sizes	8	15	35.5	16.5	20	$\odot$ 6	1/8	9.5	L-shaped swivel type — Constant flow type— <b>LSPM</b> (Brass)	1
			38.5			$\odot$ 8	1/4	12.5		2
			39.5				3/8	13.5		3
	8	15	36.5	15.75	19	$\odot$ 6	1/8	9.5	L-shaped swivel type <b>LSP</b> (Brass)	1
			39.5			$\odot$ 8	1/4	12.5		2
			42.5				3/8	13.5		3