

品名 품 명 Model	外徑 외경(mm) Outer Dia.	內徑 내경(mm) Inner Dia.	自由長 자유장(mm) Free length	密着長 밀착장(mm) Solid Length	定數 장수(kg/mm) spring constant	30万 (0.3million)		50万 (0.5million)		100万 (1million)	
						變形量 변형량(mm) Deflection	荷重 하중(kgf) Load	變形量 변형량(mm) Deflection	荷重 하중(kgf) Load	變形量 변형량(mm) Deflection	荷重 하중(kgf) Load
SR 10×15	10.5	6	15	6	1.07	7.5		6.75		6	
20			20	8	0.80	10		9		8	
25			25	10	0.64	12.5		11.25		10	
30			30	12	0.53	15		13.5		12	
35			35	14	0.46	17.5		15.75		14	
40			40	16	0.40	20		18		16	
45			45	18	0.36	22.5	8	20.25	7.2	18	6.4
50			50	20	0.32	25		22.5		20	
55			55	22	0.29	27.5		24.75		22	
60			60	24	0.27	30		27		24	
65			65	26	0.25	32.5		29.25		26	
70			70	28	0.23	35		31.5		28	
75			75	30	0.21	37.5		33.75		30	
80	80	32	0.20	40		36		32			
SR 12.5×15	12.5	7	15	6	1.20	7.5		6.75		6	
20			20	8	0.90	10		9		8	
25			25	10	0.72	12.5		11.25		10	
30			30	12	0.60	15		13.5		12	
35			35	14	0.51	17.5		15.75		14	
40			40	16	0.45	20		18		16	
45			45	18	0.40	22.5	9	20.25	8.1	18	7.2
50			50	20	0.36	25		22.5		20	
55			55	22	0.33	27.5		24.75		22	
60			60	24	0.30	30		27		24	
65			65	26	0.28	32.5		29.25		26	
70			70	28	0.26	35		31.5		28	
75			75	30	0.24	37.5		33.75		30	
80			80	32	0.23	40		36		32	
90	90	36	0.20	45		40.5		36			
100	100	40	0.18	50		45		40			
SR 14.5×20	14.5	9	20	8	1.11	10		9		8	
25			25	10	0.89	12.5		11.3		10	
30			30	12	0.74	15		13.5		12	
35			35	14	0.64	17.5		15.8		14	
40			40	16	0.56	20		18		16	
45			45	18	0.49	22.5		20.3		18	
50			50	20	0.44	25		22.5		20	
55			55	22	0.40	27.5		24.8		22	
60			60	24	0.37	30	11	27	10	24	9
65			65	26	0.34	32.5		29.3		26	
70			70	28	0.32	35		31.5		28	
75			75	30	0.30	37.5		33.8		30	
80			80	32	0.28	40		36		32	
90			90	36	0.25	45		40.5		36	
100	100	40	0.22	50		45		40			
125	125	50	0.18	62.5		56.3		50			
SR 17×25	17	11	25	10	1.51	12.5		11.3		10	
30			30	12	1.26	15		13.5		12	
35			35	14	1.08	17.5		15.8		14	
40			40	16	0.94	20		18		16	
45			45	18	0.84	22.5		20.3		18	
50			50	20	0.76	25		22.5		20	
55			55	22	0.69	27.5		24.8		22	
60			60	24	0.63	30		27		24	
65			65	26	0.58	32.5	19	29.3	17	26	15
70			70	28	0.54	35		31.5		28	
75			75	30	0.50	37.5		33.8		30	
80			80	32	0.47	40		36		32	
90			90	36	0.42	45		40.5		36	
100			100	40	0.38	50		45		40	
125	125	50	0.30	62.5		56.3		50			
150	150	60	0.25	75		67.5		60			
SR 21 x 30	21	13	30	12	2.00	15.0		13.5		12.0	
35			35	14	1.71	17.5		15.8		14.0	
40			40	16	1.50	20.0		18.0		16.0	
45			45	18	1.33	22.5		20.3		18.0	
50			50	20	1.20	25.0		22.5		20.0	
55			55	22	1.09	27.5		24.8		22.0	
60			60	24	1.00	30.0		27.0		24.0	
65			65	26	0.92	32.5	30	29.3	27	26.0	24
70			70	28	0.86	35.0		31.5		28.0	
75			75	30	0.80	37.5		33.8		30.0	
80			80	32	0.75	40.0		36.0		32.0	
90			90	36	0.67	45.0		40.5		36.0	
100			100	40	0.60	50.0		45.0		40.0	
125			125	50	0.48	62.5		56.3		50.0	
150	150	60	0.40	75.0		67.5		60.0			

品名 품 명 Model	外徑 외경(mm) Outer Dia.	內徑 내경(mm) Inner Dia.	自由長 자유장(mm) Free length	密着長 밀착장(mm) Solid Length	定數 정수(kg/mm) spring constant	30万 (0.3million)		50万 (0.5million)		100万 (1million)	
						變形量 변형량(mm) Deflection	荷重 하중(kgf) Load	變形量 변형량(mm) Deflection	荷重 하중(kgf) Load	變形量 변형량(mm) Deflection	荷重 하중(kgf) Load
SR 26 × 30	26	16.5	30	12	2,74	15	41	13,5	37	12	33
35			35	14	2,35	17,5					
40			40	16	2,06	20					
45			45	18	1,83	22,5					
50			50	20	1,64	25					
55			55	22	1,49	27,5					
60			60	24	1,37	30					
65			65	26	1,26	32,5					
70			70	28	1,17	35					
75			75	30	1,10	37,5					
80			80	32	1,03	40					
90			90	36	0,91	45					
100			100	40	0,82	50					
110			110	44	0,75	55					
125			125	50	0,66	62,5					
150			150	60	0,55	75					
175	175	70	0,47	87,5							
200	200	80	0,41	100							
SR 32 × 40	32	21	40	16	2,56	20	51	18	46	16	41
45			45	18	2,27	22,5					
50			50	20	2,04	25					
55			55	22	1,85	27,5					
60			60	24	1,70	30					
65			65	26	1,57	32,5					
70			70	28	1,46	35					
75			75	30	1,36	37,5					
80			80	32	1,28	40					
90			90	36	1,14	45					
100			100	40	1,02	50					
110			110	44	0,93	55					
125			125	50	0,82	62,5					
150			150	60	0,68	75					
175			175	70	0,58	87,5					
200			200	80	0,51	100					
250	250	100	0,41	125							
300	300	120	0,34	150							
SR 39 × 40	39	26	40	16	2,78	20	56	18	50	16	44
45			45	18	2,47	22,5					
50			50	20	2,22	25					
55			55	22	2,02	27,5					
60			60	24	1,85	30					
65			65	26	1,71	32,5					
70			70	28	1,59	35					
75			75	30	1,48	37,5					
80			80	32	1,39	40					
90			90	36	1,23	45					
100			100	40	1,11	50					
110			110	44	1,01	55					
125			125	50	0,89	62,5					
150			150	60	0,74	75					
175			175	70	0,63	87,5					
200			200	80	0,56	100					
250	250	100	0,44	125							
300	300	120	0,37	150							
SR 46 × 50	46	32	50	20	2,49	25	62	22,5	56	20	50
55			55	22	2,26	27,5					
60			60	24	2,07	30					
65			65	26	1,92	32,5					
70			70	28	1,78	35					
75			75	30	1,66	37,5					
80			80	32	1,56	40					
90			90	36	1,38	45					
100			100	40	1,24	50					
110			110	44	1,13	55					
125			125	50	1,00	62,5					
150			150	60	0,83	75					
175			175	70	0,71	87,5					
200			200	80	0,62	100					
250			250	100	0,50	125					
300			300	120	0,41	150					