



D	D ₁	T	L ₁	L ₂	ℓ	M ₁ ×P	d	A	M	R	D ₂	D ₃	H	H ₁	H ₂	A Provided bolt
20		29	5	15	38	M10×1.5	14	4	M8×18	2.0	28	19.5	14	7	8.5	CB 8—25
22	+0.020	31	8	16	42						30	21.5				
25	+0.015	36			18						10	50				
28	+0.025	39	10	20	50	M12×1.5	20	5	M10×22	3.5	36	27.5	16	8	10.5	CB10—30
32	+0.020	44			23						12	60				
38	+0.030	53	12	27	60	M16×1.5	20	6	M12×27	4.0	49	37.5	18	10	12.5	CB12—35
45	+0.025	59			32						15	70				
50	+0.035	69	15	35	70						7	M14×31				
60	+0.030	79			42	15	70	72	59.5							

Type	D	L										
MRP	20	80	90	100		110	120					
	22	80	90	100		110	120					
	25	80	90	100		110	120	130				
	28			100	110	120	130					
BRPM	32					120	130	140				
	38							140	150	160		
BRPK	45							140	150	160		
	50									160	170	
	55										170	180
	60											180

Type	D	L												
MSP	20	100	110	120	130	140								
	22			120	130	140	150							
	25			120	130	140	150							
	28				140	150	160	170						
BSPM	32						160	170	180	190				
	38								180	190	200			
BSPK	45										200	220	240	
	50										200	220		
	55											220	240	260
	60												240	260



Type - D - L

MRP - D32 - L120

BSPM - D38 - L220