



M × P	A	E	B
2 × 0.4	3.8	2	1.5
2.5 × 0.45	4.5	2.5	2
2.6 × 0.45	4.5	2.6	2
3 × 0.5	5.5	3	2.5
4 × 0.7	7	4	3
5 × 0.8	8.5	5	4
6 × 1.0	10	6	5
8 × 1.25	13	8	6
10 × 1.5	16	10	8
12 × 1.75	18	12	10

M	SCM435(M3~M20) - SCM440(M24)
H	38~43HRC (M3~M20) 32~37HRC (M24)
S	Surface Treatment: Black Oxide Screw Precision JIS B 1176 Strength Class 12.9 (M3~M20)

Part Number	Type	M-	L	ℓ
CB 2-			4	Studs Fully Threaded
			5	
			6	
			8	
			10	
			12	
CB 2.5-			4	Studs Fully Threaded
			5	
			6	
			8	
			10	
			12	
CB 2.6-			4	Studs Fully Threaded
			5	
			6	
			8	
			10	
			12	
CB 3-			5	Studs Fully Threaded
			6	
			8	
			10	
			12	
			14	
			15	
			16	
			18	
			20	
			22	
			25	
			30	18
			35	
			40	
			45	
			50	
			55	

Part Number	Type	M-	L	ℓ
CB 4-			5	Studs Fully Threaded
			6	
			8	
			10	
			12	
			14	
			15	
			16	
			18	
			20	
CB 5-			5	Studs Fully Threaded
			6	
			8	
			10	
			12	
			14	
			15	
			16	
			18	
			20	
			22	20
			25	
			30	
			35	
			40	
			45	
			50	
			55	
			60	
			65	
			70	24
			75	
			80	
			85	
			90	
			95	

Part Number	Type	M-	L	ℓ
CB 6-			6	Studs Fully Threaded
			8	
			10	
			12	
			14	
			15	
			16	
			18	
			20	
			22	
			25	
			30	
			35	
			40	
50				
55				
60				
65				
70				
75				
80				
85				
90				
			95	24

Part Number	Type	M-	L	ℓ				
CB 8-			8	Studs Fully Threaded				
			10					
			12					
			15					
			16					
			18					
			20					
			22					
			25					
			30					
			35					
			40					
			45					
			50					
							55	28
60								
65								
70								
75								
CB 10-				10			Studs Fully Threaded	
12								
15								
20								
25								
30								
35								
40								
45								
50								
			55	32				
			60					
			65					
			70					
			CB 12-				15	Studs Fully Threaded
			20					
			25					
			30					
			35					
			40					
45								
50								

Order Example

TYPE	M	L
CB3	-	20