



D	D <sub>1</sub>	A	B	a	b	d	H	H <sub>1</sub>	T	(Q)	Ls	M <sup>Stopper distance</sup>	ℓ	a <sub>1</sub>	b <sub>1</sub>	ϕH <sub>7</sub>	⑥ Provided bolt	⑦ Provided dowel pins	
20	26	74	44	56	30	6.6	30	50	15	42	50	0 ~ 20	56	28	15	6 <sup>+0.012</sup> <sub>0</sub>	CB 6-30	MSTM 6-20	
25	31	84	48	66	30	9	30	50	20	46	50	0 ~ 20	66	33	15	8	CB 8-35	MSTM 8-30	
32	40	100	58	76	36	11	40	60	20	56	60	0 ~ 25	76	38	18	8 <sup>+0.015</sup> <sub>0</sub>		MSTM 8-30	
38	48	130	75	100	44	11	50	70	25	73	70	0 ~ 29	100	50	22	10		CB10-45	MSTM10-40
50	60	155	90	125	60	14	65	90	25	87	90	0 ~ 42	125	62.5	30	10		CB12-50	MSTM10-40

TYPE	D	L															
MYA MYAP MYJ MYJP	20	90	100	110	120												
						130	140	150	160								
	25	90	100	110	120												
						130	140	150	160								
									170	180	200						
	32				110	120	130	140	150								
								160	170	180	200						
											220	240	260				
	38							130	140	150	160						
											170	180	200	220			
														240	260	300	
	50										170	180	200				
												220	240	260			
															300	350	

Type	Replacement parts					
	Post	Holder	Bushing	Retainer	Spring	Stopper
MYA	—	MGH	MAB	MBS	SWMY	STMY
MYAP		MGHP	MABP			
MYJ		MGH	MAB	MBJ		
MYJP		MGHP	MABP			



Order Example

TYPE	D	L
MYAP32	-	150