



	<b>M</b>	<b>TYPE</b>		<b>Usage temperature</b> Use under temperate 80°C
Lock holder	S50C	Normal bushing	Slim bushing	
Lock Bushing	SK3	<b>MPLK</b>	<b>MPLKS</b>	

Standard Type . Heat Proof Standard Type

Part Number	Max. usable load 2 sets under	L	L <sub>1</sub>	L <sub>2</sub>	T	H	H <sub>1</sub>	J	K	P	P <sub>1</sub>	P <sub>2</sub>	A	A <sub>1</sub>	t	t <sub>1</sub>	d	d <sub>1</sub>	<b>A</b> 2 pcs. each
<b>MPLK</b> (Normal bushing)	<b>10</b> 981N {100kgf}	48	36	25	42	22	18	2	2	36	24	22	24	16	9.5	18	11	6.5	CB6 - 20 CB6 - 30
	<b>20</b> 1961N {200kgf}	54	42							40	28				9	16			CB6 - 20 CB6 - 25
	<b>30</b> 2942N {300kgf}	65	46	35	48.5	25	20	3.5	3.5	50	31	26	27	19	9.5	17	14	9	CB6 - 30 CB6 - 35
	<b>60</b> 5884N {600kgf}	73	50							52	33								CB8 - 30 CB8 - 35
	<b>*80S</b> 7845N {800kgf}									11.5	34								
	<b>100</b> 9807N {1000kgf}	103	65	48	58	30	24	4	4	76	42	31	34	25	13	19	17	11	CB10 - 30 CB10 - 35
<b>MPLKS</b> (Slim bushing)	<b>30</b> 2942N {300kgf}	65	46	35	48.5	25	20	3.5	3.5	50	31	26	24	19	9.5	15.5	11	7	CB6 - 25 CB6 - 30
	<b>60</b> 5884N {600kgf}	73	50							52	33								CB8 - 25 CB8 - 30
	<b>*80S</b> 7845N {800kgf}			56.5	11.5	34													

T of dimension of MPLK80S and MPLKS80S are 56.5, and K dimension of them are 11.5

Long Type . Heat Proof Long Type

Part Number	Max. usable load 2 sets under	L	L <sub>1</sub>	L <sub>2</sub>	T	H	H <sub>1</sub>	J	K	P	P <sub>1</sub>	P <sub>2</sub>	A	A <sub>1</sub>	t	t <sub>1</sub>	d	d <sub>1</sub>	<b>A</b> 2 pcs. each
<b>MPLK</b> (Normal bushing)	<b>60L</b> 5884N {600kgf}	73	50	35	79.5	25	20	3.5	34.5	52	33	57	27	19	9.5	17	14	9	CB8 - 30 CB8 - 35
	<b>80</b> 7845N {800kgf}				87.5														
	<b>100L</b> 9807N {1000kgf}	103	65	48	89	30	24	4	35	76	42	62	34	25	13	19	17	11	CB10 - 30 CB10 - 35
<b>MPLKS</b> (Slim bushing)	<b>80</b> 7845N {800kgf}	73	50	35	87.5	25	20	3.5	42.5	52	33	65	24	19	9.5	15.5	14	9	CB8 - 25 CB8 - 30



Order Example

TYPE	No.
<b>MPLK30</b>	