



- ⦿ Oil grooves
- ⦿ Oil groove part might not be colored by heat treatment.
- ⦿ There may be a center hole on the end.
- ⦿ Designate N=8 when press-fit processing is not required.

TYPE	Part Number	M	H
Pre-fit length designation	SP	SUJ2	58HRC ~ Induction hardening

Sliding Parts Df6	Press Fot Section Dk6	H	M(Coarse thread)		TYPE	D	L increment 5 mm	N increment 1 mm
			M × Pitch	ℓ				
13 -0.016 -0.027	13	16	M6×1.0	12	SP	13	60 ~ 90	8 ~ 60
							95 ~ 120	
16	16	19	M10×1.5	20	SP	16	80 ~ 110	
							115 ~ 150	
							155 ~ 180	
20	20	23	M12×1.75	24	SP	20	185 ~ 210	
							90 ~ 130	
							135 ~ 170	
							175 ~ 210	
25 -0.020 -0.033	25	28	M16×2.0	32	SP	25	215 ~ 250	
							255 ~ 300	
							100 ~ 140	
30	30	35	M16×2.0	32	SP	30	145 ~ 190	
							195 ~ 250	
							255 ~ 300	
35 -0.025	35	40	M16×2.0	32	SP	35	150 ~ 200	
							205 ~ 250	
							255 ~ 300	
40 -0.041	40	45	M16×2.0	32	SP	40	305 ~ 350	
							150 ~ 200	
							205 ~ 250	



Order Example

TYPE	D	L	N
SP	- D20	- L230	- N30