

**Guide holders**

Ⓚ (Q) values are reference only.  
Ⓚ When assembling on site, press-fit using a hydraulic press.

FC250

Type	Dk6	A	B	a	b	d	H	T	(Q)	M	øH7	ℓ	a1	b1	
MGH	20	+0.002 -0.011	74	44	56	30	6.6	30	15	42	6	+0.012 0	56	28	15
	25		84	48	66	30	9	30	20	46	8		66	33	15
MGHP	32		100	58	76	36	11	40	20	56	8	+0.015 0	76	38	18
	38	+0.003 -0.013	130	75	100	44	11	50	25	73		10		100	50
	50		155	90	125	60	14	65	25	87	12		125	62.5	30
	60	+0.004 -0.014	190	120	150	80	18	75	30	117		13	+0.018 0	150	75
80		230	150	180	110	22	100	35	145	16		190	90	55	

**Plain guide bushings**

Ⓚ (Q) values are reference only.

FC250

**Oil-free guide bushings**

Ⓚ (Q) values are reference only.

FC250  
Special solid lubricant (embedded)

Type	D	A	B	a	b	d	H1	T	(Q)	øH7	ℓ	a1	b1		
MGB	20	+0.041 +0.031	74	44	56	30	6.6	40	15	42	6	+0.012 0	56	28	15
	25		84	48	66	30	9	45	20	46	8		66	33	15
MGBP	32	+0.047 +0.037	100	58	76	36	11	50	20	56	8	+0.015 0	76	38	18
	38	+0.049 +0.037	130	75	100	44	11	60	25	73		10		100	50
	50	+0.052 +0.037	155	90	125	60	14	85	25	87	12		125	62.5	30
	60	+0.061 +0.043	190	120	150	80	18	100	30	117		13	+0.018 0	150	75
MGBZP	80	+0.063 +0.043	230	150	180	110	22	130	35	145	16		190	90	55

- Type - D
- MGH - D50
  - MGB - D38